

2018
Virginia Department of Transportation
Daily Traffic Volume Estimates
Including Vehicle Classification Estimates
where available

Special Locality Report
206
Town of Dayton

Information in this report is included in Report
82
(Rockingham County)

Prepared By
Virginia Department of Transportation
Traffic Engineering Division

In Cooperation With
U.S. Department of Transportation
Federal Highway Administration

Virginia Department of Transportation
Traffic Engineering Division
Traffic Monitoring Section

The Virginia Department of Transportation (VDOT) conducts a program where traffic count data are gathered from sensors in or along streets and highways and other sources. From these data, estimates of the average number of vehicles that traveled each segment of road are calculated. VDOT periodically publishes booklets listing these estimates.

One of these booklets, titled "Average Daily Traffic Volumes with Vehicle Classification Data, on Interstate, Arterial and Primary Routes" includes a list of each Interstate and Primary highway segment with the estimated Annual Average Daily Traffic (AADT) for that segment. AADT is the total annual traffic estimate divided by the number of days in the year. This booklet also includes information such as estimates of the percentage of the AADT made up by 6 different vehicle types, ranging from cars to double trailer trucks; estimated Annual Average Weekday Traffic (AAWDT), which is the number of vehicles estimated to have traveled the segment of highway during a 24 hour weekday averaged over the year; as well as Peak Hour and Peak Direction factors used by planners to formulate design criteria.

In addition to the Primary and Interstate publication, one hundred books are published periodically, one for each of 100 areas across the state defined by VDOT for record-keeping purposes. These books include traffic volume estimates for roads within the county, cities, and towns within the area. These books are titled "Daily Traffic Volumes Including Vehicle Classification Estimates, where available; Jurisdiction Report numbers 00 through 99".

Also available are a number of reports summarizing the average Vehicle Miles Traveled (VMT) in selected jurisdictions and other categories of highways. There are many different ways to present traffic volume summary information. Because the user determines the value of each presentation, the reports have been redesigned based on user requests and feedback. The people of the VDOT Traffic Engineering Division Traffic Monitoring Section who produce these books welcome requests for other helpful ways of presenting the summary information.

A compact disc (CD) is available that includes files in the Adobe® Portable Document Format (PDF) that can be displayed, searched, and printed using common desktop computer equipment. The CD includes the publications described above as well as a number of other reports, including specialized VMT summaries and smaller AADT reports for each city and town separately.

Publication Notes

Parallel Roads

For road inventory and management purposes, some roadways are counted separately by direction and have separately published traffic estimates for each direction of travel. Examples of such roadways are the interstate system and routes with separated facilities and (usually) one-way traffic facilities in urban areas. In these publications, they are referred to as parallel roads. As a convenience for the users of the publication, the listing for segments of roads with parallel segments are published with both the traffic estimates for their own direction of travel (e.g. I-95 Northbound) as well as the estimate of the total of all traffic on the same route including parallel roadways (all directions of I-95). The publication will have a "Combined Traffic Estimates for Parallel Roadways on this Route" or "Combined Traffic" identifiers for the combined direction of travel estimates.

Roadways such as I-395 with a North segment, a South segment and a separate Reversible lane segment will have the estimate for more than two parallel roadways included in the entire combined traffic estimate.

Some routes have very complicated paths through cities and towns. These parallel paths may be too complex to allow a relationship between nearby sections of the opposite direction on the same route. In this case, to indicate that the traffic estimates for such a road segment may not include all directions of traffic on that route, the line that would list the combined values will indicate "NA" for not available.

VDOT's traffic monitoring program includes more than 100,000 segments of roads and highways ranging from several mile sections of Interstate highways to very short sections of city streets. Due to problems experienced obtaining some traffic count data, and the level of quality necessary to maintain confidence in the data, no estimate is currently available for some segments of roadway. These segments are included in the publications indicating "NA" for not available. It is the intention of the VDOT Traffic Engineering Division Traffic Monitoring group to obtain the data necessary and to report traffic volume estimates on all road segments included in these publications.

Many of the road segments in this program are local secondary roads. The amount and detail of data collected on these roads are not as great as the data collected on higher volume roads. The vehicle classification, average weekday traffic volumes, and the theoretical design hour traffic volumes are not calculated for these roads. The publications indicate "NA" for the information that is not available.

This publication is based on a traffic monitoring program initiated in 1997. Because the data collection techniques and statistical evaluation processes are different than those used in previous years, comparison with previous publications may be misleading.

Glossary of Terms:

Route: The Route Number assigned to this segment of roadway with the master inventory route number if this is an overlapping route, with official street or highway name if available.

Length: Length of the traffic segment in miles.

AADT: Annual Average Daily Traffic. The estimate of typical daily traffic on a road segment for all days of the week, Sunday through Saturday, over the period of one year.

QA: Quality of AADT:

- A Average of Complete Continuous Count Data
- B Average of Selected Continuous Count Data
- F Factored Short Term Traffic Count Data
- G Factored Short Term Traffic Count Data with Growth Element
- H Historical Estimate
- M Manual Uncounted Estimate
- N AADT of Similar Neighboring Traffic Link
- O Provided By External Source
- R Raw Traffic Count, Unfactored

4Tire: Percentage of the traffic volume made up of motorcycles, passenger cars, vans and pickup trucks.

Bus: Percentage of the traffic volume made up of busses.

2Axle Truck: Percentage of the traffic volume made up of 2 axle single unit trucks (not including pickups and vans).

3+Axle Truck: Percentage of the traffic volume made up of single unit trucks with three or more axles.

1Trail Truck: Percentage of the traffic volume made up of units with a single trailer.

2Trail Truck: Percentage of the traffic volume made up of units with more than one trailer.

QC: Quality of Classification Data:

- A Average of Complete Continuous Count Data
- B Average of Selected Continuous Count Data
- C Short Term Classified Traffic Count Data
- F Factored Short Term Traffic Count Data
- H Historical Estimate
- M Mass Collective Average
- N Classification Estimates of Similar Neighboring Traffic Link

K Factor: The estimate of the portion of the traffic volume traveling during the peak hour or design hour.

QK: Quality of the K Factor estimate:

- A Factor based on 30th Highest Hour Observed During at least 250 days of Continuous Traffic Data
- B Factor based on other Hour Observed During Less than 250 days of Continuous Traffic Data
- F Factor based on Highest Hour Collected at in a 48 Hour Weekday Period
- M Factor based on Manual Estimate of design hour
- N Design Hour Factor (K Factor) of Similar Neighboring Traffic Link
- O Provided by External Source

Dir Factor: The estimate of the portion of the traffic volume traveling in the peak direction during the peak hour..

AAWDT: Average Annual Weekday Traffic. The estimate of typical traffic over the period of one year for the days between Monday through Thursday inclusive.

QW: Quality of AAWDT:

- A Average of Complete Continuous Count Data
- B Average of Selected Continuous Count Data
- F Factored Short Term Traffic Count Data
- G Factored Short Term Traffic Count Data with Growth Element
- M Manual Uncounted Estimate
- N AAWDT of Similar Neighboring Traffic Link
- O Provided by External Source

Year: Year for which the published values are appropriate. If the Quality of AADT (QA) is "R", the year is the year that the raw traffic count was collected, and if available,

Route Shield Legend

Route Systems

-  Interstate Route Traffic volume data for Interstate Routes and some other routes are reported separately by direction, as well as combined.
-  US Route
-  Virginia State Route
-  Frontage Road (F precedes frontage route number)
-  Secondary Route

Special Routes

-  Bus - Business Route
-  Bypass - Bypass Route
-  Truck - Truck Route
-  ALT - Alternate Route
-  Wve - Wve Route connector
-  P - Parallel Route; Southbound or Westbound direction lanes of a numbered route where they are on a different road facility than the other direction.
-  The VDOT Maintenance Jurisdiction number is displayed below the Secondary Route Number if the Maintenance Jurisdiction is different than the jurisdiction in the title of the report.

Virginia Department of Transportation
 Traffic Engineering Division
 2018
 Annual Average Daily Traffic Volume Estimates By Section of Route
 Town of Dayton

Route	Jurisdiction	Length	AADT	QA	4Tire	Bus	-----Truck-----				QC	K Factor	QK	Dir Factor	AAWDT	QW
							2Axle	3+Axle	1Trail	2Trail						
From: SCL Dayton 42 257 John Wayland Hwy	Town of Dayton (Maint: 82)	0.42	12000	N	95%	1%	1%	1%	2%	0%	N	0.104	F	0.527	14000	N
To: BUS SR 42 42 John Wayland Hwy	Town of Dayton (Maint: 82)	0.45	16000	A	97%	0%	1%	1%	1%	0%	C	0.112	A	0.52	17000	A
From: NCL Dayton																
From: SR 257 Mason St Bus 42 Main St	Town of Dayton (Maint: 82)	0.12	1800	F	97%	0%	1%	2%	1%	0%	F	0.112	F	0.608	2000	F
To: S SR 290 Huffman Dr																
From: SR 290 S Huffman Dr Bus 42 290 Main St	Town of Dayton (Maint: 82)	0.07	3200	F	97%	0%	1%	2%	1%	0%	F	0.105	F	0.546	3500	F
To: SR 290 N College St																
From: SR 290 N College St Bus 42 Main St	Town of Dayton (Maint: 82)	0.60	1200	F	97%	0%	1%	2%	1%	0%	C	0.097	F	0.56	1300	F
To: NCL Dayton																
From: WCL Dayton																
From: WCL Dayton 257 Ottobine Rd	Town of Dayton (Maint: 82)	0.42	4200	N	95%	1%	2%	1%	1%	0%	N	0.102	F	0.563	4500	N
To: W SR 42 Bus																
From: E RT 42 BUS 257 42 John Wayland Hwy	Town of Dayton (Maint: 82)	0.42	12000	N	95%	1%	1%	1%	2%	0%	N	0.104	F	0.527	14000	N
To: CL Dayton																
From: ECL Dayton																
From: ECL Dayton 290 Huffman Dr	Town of Dayton (Maint: 82)	0.15	8100	F	97%	2%	0%	0%	0%	0%	F	0.095	F	0.521	8600	F
To: SR 42 John Wayland Hwy																
From: SR 42 John Wayland Hwy 290 Huffman Dr	Town of Dayton (Maint: 82)	0.06	1800	F	97%	2%	0%	0%	0%	0%	F	0.118	F	0.639	1900	F
To: S SR 42 Bus																
From: S SR 42 Bus Bus 290 42 Main St	Town of Dayton (Maint: 82)	0.07	3200	F	97%	0%	1%	2%	1%	0%	F	0.105	F	0.546	3500	F
To: N SR 42 BUS																
From: N SR 42 BUS 290 College St	Town of Dayton (Maint: 82)	0.33	2000	F	97%	2%	0%	0%	0%	0%	C	0.130	F	0.568	2100	F
To: NCL Dayton																

Virginia Department of Transportation
Traffic Engineering Division
2018
Annual Average Daily Traffic Volume Estimates By Section of Route
Town of Dayton

Route	Length	AADT	QA	4Tire	Bus	-----Truck-----				QC	K Factor	QK	Dir Factor	AAWDT	QW	Year	
						2Axle	3+Axle	1Trail	2Trail								
732 82 Bowman Rd	0.06	2000	F	94%	1%	1%	1%	3%	0%	F	0.156	F	0.554	2200	F	2018	
						From: 82-1207 High St											
						To: SR 290 Gap											
1201 82 Turner St	0.08	30	R								NA			NA		07/30/2012	
						From: 82-1203 West View St											
						To: 82-1204 Ashby St											
1202 82 Sunset Dr	0.17	250	R								NA			NA		07/30/2012	
						From: SR 257 Ottobine Rd											
						To: 82-1209 Thompson											
1202 82 Sunset Dr	0.12	210	R								NA			NA		07/30/2012	
						From: SR 257 Ottobine Rd											
						To: WCL Dayton: 82-1208											
1203 82 West View St	0.45	580	R								NA			NA		07/30/2012	
						From: SR 257 Ottobine Rd											
						To: 82-732 Bowman Rd											
1204 82 Ashby St	0.45	510	F	93%	6%	1%	0%	0%	0%	C	0.278	F	0.692	550	F	2018	
						From: SR 257 Ottobine Rd											
						To: 82-732 Bowman Rd											
1205 82 Summit St	0.16	120	R								NA			NA		07/30/2012	
						From: SR 257 Ottobine Rd											
						To: 82-1209 Thompson											
1205 82 Summit St	0.12	100	R								NA			NA		07/30/2012	
						From: SR 257 Ottobine Rd											
						To: 82-1208 Mill St											
1206 82 East View St	0.12	230	R								NA			NA		07/30/2012	
						From: SR 257 Ottobine Rd											
						To: 82-1209 Thompson											
1206 82 East View St	0.13	140	R								NA			NA		07/30/2012	
						From: SR 257 Ottobine Rd											
						To: 82-1208 Mill St											
1207 82 High St	0.40	200	R								NA			NA		07/30/2012	
						From: SR 257 Ottobine Rd											
						To: 82-1209 Thompson											
1208 82 Mill St	0.56	620	R								NA			NA		04/10/2018	
						From: WCL Dayton											
						To: Bus SR 42											
1209 82 Thompson	0.07	230	R								NA			NA		06/23/2015	
						From: 82-1202 Sunset Dr											
						To: 82-1203 West View St											
1209 82 Thompson	0.09	320	R								NA			NA		06/23/2015	
						From: 82-1203 West View Ave											
						To: 82-1204 Ashby St											
1209 82 Thompson	0.26	330	R								NA			NA		07/30/2012	
						From: 82-1204 Ashby Ave											
						To: 82-1207 High St											
1210 82 Stover	0.09	90	R								NA			NA		07/30/2012	
						From: 82-1203 West View St											
						To: 82-1204 Ashby St											
1210 82 Stover St	0.09	45	R								NA			NA		07/30/2012	
						From: 82-1205 Summit Ave											
						To: SR 257; Bus SR 42											
1211 82	0.10	490	R								NA			NA		03/31/2009	
						From: SR 42 John Wayland Hwy											
						To: Dead End											
1212 82	0.23	630	R								NA			NA		04/10/2018	
						From: 82-732 Bowman Rd											
						To: SR 257 Ottobine Rd											
1225 82	0.18	330	R								NA			NA		04/10/2018	
						From: SR 257 Ottobine Rd											
						To: 82-1209											

Virginia Department of Transportation
 Traffic Engineering Division
 2018
 Annual Average Daily Traffic Volume Estimates By Section of Route
 Town of Dayton

Route	Length	AADT	QA	4Tire	Bus	-----Truck-----				QC	K Factor	QK	Dir Factor	AAWDT	QW	Year
						2Axle	3+Axle	1Trail	2Trail							
Town of Dayton																
① ₈₂ 1226	0.08	100	R			From: End State Maintenance					NA			NA		04/10/2018
						To: 82-1225										
① ₈₂ 9370 Metts Dr	0.46	320	R			From: 82-732 Turner Rd					NA			NA		04/10/2018
						To: Ashby High Sch										
① ₈₂ 9370 Metts Dr	0.04	290	R			From: 0.46 MN 82-732 Turner Rd					NA			NA		04/10/2018
						To: 0.50 MN 82-732 Turner Rd										
① ₈₂ 9370 Metts Dr	0.05	440	R			From: 0.50 MN 82-732 Turner Rd					NA			NA		04/10/2018
						To: Dayton Elem Sch										